

CEMproof® CEMstar Adhesive

-Building Adhesive and Joint Sealant-

Product

CEMstar is a one-component, solvent-containing, plasto-elastic building adhesive / joint sealant. Joint sealer based on polycarbon ester which sticks very well to almost any surface even to wet, oil or bituminous materials.

Field of application

- Sealing and repairing of concrete joints, particularly in foundation and roof areas.
- Air-tight luting of vapour seals on most various rounds
- Ideal product to affix swelling tapes (e.g. QUELLMAX, CEMswell)



Features

- CEMstar can also be used in rainy weather condition
- good adhesion to moisture, oil, bitumen
- resisting to UV and atmospheric exposure
- resisting against ozone and micro organisms
- agrees well with paint coats
- suitable also for submarine use
- silicone-free

Standard colour usually transparent, on request also available in particular colours. Shelf life of the original tape amounts to approx. 24 months when being stored cool and dry.

Technical Data

Character:	plasto-elastic
Colour shade:	clear / transparent
Density:	approx. 1.05 g/cm ³
Development of skin:	immediate wet strength
Working temperature :	+5 °C up to +40 °C
Resistance to temperature:	-25 °C up to +95 °C

Form of Delivery / Storage

300 ml cartridge, 20 cartridges/box, 60 boxes/pallet

Shelf life 2 years at room temperature.

Safety Note

Flammable! Repeated contact can lead to dry or rough skin. Vapours can cause sleepiness or drowsiness. Do not inhale vapour. Avoid contact with eyes or skin. Dispose of empty containers safely.

**CEMstar - not only a bonding agent!
CEMstar is a unique adhesive and joint filler!**



CEMstar adhesive and joint filler is a unique technology **made in Germany.**